

In the Claims:

Please cancel Claims 1-4 and 15; and amend Claims 5 and 8 as follows. This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Cancelled)

2. (Cancelled)

3. (Cancelled)

4. (Cancelled)

5. ~~The lock box of claim 1,~~ A lock box for a trailer hitch receiver,
comprising:
a polygonal container having at least three sides and a base defining an interior
compartment for holding small items, each of the at least three sides and the base being sized and
positioned for selective receipt of the container substantially within a main cavity of a trailer
hitch receiver wherein two of the three sides define opposed apertures for receipt of a pin having
an engaged position with respect to corresponding holes in the receiver hitch to selectively retain
the container within the main cavity of the trailer hitch receiver and a disengaged position to
allow release of the container from the main cavity.

including a first side of the at least three sides of the container having a selective open position to allow access to the interior compartment of the container and a selective closed, lockable position; and

a lock coupled to the container to deter access to the interior compartment of the container.

6. (Original) The lock box of claim 5 wherein the lock is a combination lock.

7. (Original) The lock box of claim 5 wherein the lock is coupled to the first side of the container.

8. (Presently Amended) A lock box for a trailer hitch receiver, comprising:
an elongated tube sized for selective receipt substantially within a main cavity of a trailer hitch receiver, the tube having an ~~operable~~ openable front wall, a back wall, and a side wall defining an openable interior compartment for holding small items, wherein the side wall defines opposed first and second apertures, the first and second apertures positioned so as to be each substantially alignable with a corresponding first and second side holes in the trailer hitch receiver when the tube is positioned substantially within the main cavity of the trailer hitch receiver for receipt of a retaining pin; and,

a lock coupled to the ~~operable~~ openable front wall to deter access to the interior compartment of the tube.

9. (Original) The lock box of claim 8 including a retaining pin having a first position wherein the pin is received in the apertures and the holes to selectively retain the tube when the tube is positioned substantially within the main cavity, and a second position wherein the pin is not received in the apertures and the holes to allow removal of the tube from the main cavity of the trailer hitch receiver.

10. (Original) The lock box of claim 9 wherein the side wall includes parallel spaced apart first and second sides, including a first slot in the first side and a second slot in the second side, and further including a first and a second pin retaining member, the first and the second slot each configured to selectively receive the respective first and second pin retaining member.

11. (Original) The lock box of claim 10 wherein the retaining pin has first and second circumferential grooves and wherein the first pin retaining member has a distal end configured to selectively engage the first circumferential groove in the retaining pin and the second pin retaining member also has a distal end configured to selectively engage the second circumferential groove in the retaining pin.

12. (Original) The lock box of claim 10 wherein the side wall includes parallel top and bottom walls.

13. (Original) The lock box of claim 8 wherein the lock is positioned on the front wall of the tube, and a dust flap coupled to the lock has an open position to provide access to the lock and a closed position to cover the lock.

14. (Original) The lock box of claim 8 wherein the lock is a keyless lock.

15. (Canceled)